


60TL










IT ISTRUZIONI DI MONTAGGIO
FR INSTRUCTIONS DE MONTAGE
EN MOUNTING INSTRUCTIONS
DE MONTAGEANLEITUNG
NL MONTAGEVOORSCHRIFT
ES GUÍA DE MONTAJE
PT INSTRUÇÕES DE MONTAGEM
PL INSTRUKCJA MONTAŻU
CZ NÁVOD K MONTÁŽI
RO INSTRUȚIUNI DE MONTARE
HU SZERELÉSI ÚTMUTATÓ
FI ASENNUSOHJEET
SK NÁVOD NA MONTÁŽ
SL NAVODILA ZA MONTAŽO
MK ИНСТРУКЦИЈА ЗА МОНТАЖА
AL UDHËZIME PËR MONTIMIN
EL ΟΔΗΓΙΕΣ ΣΥΝΑΡΜΟΛΟΓΗΣΗΣ
HE הוראות הרכבה


Meliconi S.p.A. - V. Minghetti, 10
40057 Cadiano di Granarolo E. (BO) Italy
www.meliconi.com e-mail: info@meliconi.com

IT Attrezzatura per montaggio FR Outils d'assemblage EN Assembly equipment ES Herramientas de montaje



IT Dati tecnici FR Caractéristiques techniques EN Technical data ES Datos técnicos





GE - EN CALIBRATION - ES CALIBRACIÓN

18

Diagram 18 illustrates the process of mounting the rear plate to the back of the monitor. The diagram shows the rear plate with two vertical rails. Two circular callouts labeled 'A' indicate the specific locking mechanism. A central circular callout shows a close-up of the locking pin being inserted into the rail, with a '(x2)' label indicating that this step is repeated for both sides.

¡ATENCIÓN! Ninguno de estos pomos debe desatornillarse por completo.

[illegible]